

STO CONCRETE BLOCK PLASTER SYSTEM

StoArmat Reinforced Plaster System

To combat fractures and stress that can occur in concrete block construction during the curing and settling process. The **StoFlexyl waterproofing membrane** is to ensure openings, junctions, terminations and overlays are waterproofed.

**SS202 STOARMAT MIRAL PLASTER SYSTEM BRANZ APPRAISAL CERTIFICATE No.515
INCORPORATING:**

1. *Stoflexyl Waterproofing* 18Kg pail plus cement evaluated by BRANZ to meet AS/NZS4858 waterproofing membrane requirements as required by NZBC E2/AS1
2. *Levellite Base Plaster* 20Kg bag mineral fibre reinforced based plaster with EPS bead for levelling and straightening walls. Can be machine applied
3. *StoArmat Classic Plaster* 23Kg pail European fibre reinforced non-cement based crack resistant plaster used with European mesh as a reinforcement plaster
4. *Stolit Coloured Finishing Render* in 25Kg Pail
 - Stolit K* - 1.0mm Coloured Float Finish Render
 - 1.5mm Coloured Float Finish Render
 - 2.0mm Coloured Float Finish Render
 - 3.0mm Coloured Float Finish Render
 - Stolit* - MP Fine Sponge or Adobe Coloured Finishing Render
 - MP Natural Sponge or Adobe Coloured Finishing Render
 - Milano Smooth or Adobe Coloured Finishing Render

STO CONCRETE BLOCK	STO CONCRETE BLOCK PLASTER SYSTEM	CB 006
		2014

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.