

STO CONCRETE BLOCK INSULATION SYSTEM

SS207 STOTHERM MASONRY INSULATION SYSTEM BRANZ APPRAISAL CERTIFICATE NO. 604
INCORPORATING:

1. STOTHERM PANEL (EPS) SELF-EXTINGUISHING PANEL MANUFACTURED TO AS1366 PT BY AN APPROVED MANUFACTURER (*in 40mm, 50mm, 60mm, 80mm & 100mm thickness*)
2. STOFLEXYL WATERPROOFING 18kg PAIL PLUS CEMENT EVALUATED BY BRANZ TO MEET AS/NZS4858 AS A WATERPROOFING MEMBRANE OVER PLASTER SUBSTRATES IN ACCORDANCE WITH NZBC E2/AS1
3. MULTISCREED PLASTER 25kg BAG BASECOAT PLASTER TO STRAIGHTEN AND PROVIDE A SOLID BASECOAT
4. STOARMAT CLASSIC PLASTER 23kg PAIL EUROPEAN FIBRE REINFORCED NON-CEMENT BASED CRACK RESISTANT PLASTER USED WITH EUROPEAN MESH AS A REINFORCEMENT PLASTER
5. STOLIT K or MP COLOURED RENDER 25kg PAIL EUROPEAN FIBRE REINFORCED NON-CEMENT BASED COLOURED FINISHING RENDER AVAILABLE IN STOLIT K 1.0/1.5/2.0/3.0mm FLOAT FINISH & STOLIT MP, MP NATURAL & MILANO FINE FINISH
6. STOCOLOR : MAXICRYL FACADE PAINT 15lt PAIL
: LASTIC SATIN FACADE PAINT 15lt
: LOTUSAN FLAT MINERAL PAINT 15lt PAIL

STO CONCRETE BLOCK	STO CONCRETE BLOCK INSULATION SYSTEM	STCB 003
	INTRODUCTION	2014

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.