



**STOTHERM MASONRY INSULATION SYSTEM - SS207**

- STO ADHESIVE MORTAR
- SELECTED STOTHERM PANELS - 600Hx1200Wx40, 50, 60, 80 & 100mm THICK
- BASECOAT: MULTISCREED 4-5mm
- REINFORCEMENT: STOARMAT CLASSIC PLUS: STO EUROPEAN MESH
- REINFORCEMENT: STOARMAT CLASSIC
- FINISHING RENDER: STOLIT K COLOURED FINISHING RENDER - 1.0, 1.5, 2.0 & 3.0mm FLOAT FINISH
- COATING/STOCOLOR MAXICRYL MATT FACADE PAINT  
LASTIC SATIN FACADE PAINT  
LOTUSAN MINERAL RESIN PAINT

NOTE:  
60mm STOTHERM PANELS REQUIRE COUNTER SUNK FIXINGS

SCALE 1:20

<b>STO CONCRETE BLOCK</b>	<b>STO CONCRETE BLOCK INSULATION SYSTEM</b>	<b>STCB 100</b>
	<b>STOTHERM INSULATION SYSTEM - ISOMETRIC</b>	<b>2014</b>

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.