

STO CONCRETE BLOCK INSULATION SYSTEM

SS207 STOTHERM MASONRY INSULATION SYSTEM BRANZ APPRAISAL CERTIFICATE NO. 604
INCORPORATING:

1. STOTHERM PANEL (EPS) SELF-EXTINGUISHING PANEL MANUFACTURED TO AS1366 PT B (*in 40mm, 50mm, 60mm, 80mm & 100mm thickness*)
2. STOFLEXYL WATERPROOFING 18kg PAIL PLUS CEMENT EVALUATED BY BRANZ TO MEET AS/NZS4858 AS A WATERPROOFING MEMBRANE OVER RENDER SUBSTRATES IN ACCORDANCE WITH NZBC E2/AS1
3. MULTISCREED RENDER 25kg BAG BASECOAT RENDER TO STRAIGHTEN AND PROVIDE A SOLID BASECOAT
4. STOARMAT CLASSIC RENDER 23kg PAIL EUROPEAN FIBRE REINFORCED NON-CEMENT BASED CRACK RESISTANT RENDER USED WITH EUROPEAN MESH AS A REINFORCEMENT PLASTER
5. STOLIT K or MP COLOURED RENDER 25kg PAIL EUROPEAN FIBRE REINFORCED NON-CEMENT BASED COLOURED FINISHING RENDER AVAILABLE IN STOLIT K 1.0/1.5/2.0/3.0mm FLOAT FINISH & STOLIT MP, MP NATURAL & MILANO FINE FINISH
6. STOCOLOR : STOCOLOR MAXICRYL MATT FACADE PAINT 15lt PAIL
: STOCOLOR LASTIC SATIN FACADE PAINT 15lt
: STOCOLOR LOTUSAN FLAT MINERAL PAINT 15lt PAIL

STOTHERM MASONRY	STOTHERM MASONRY INSULATION SYSTEM	STM 003
	INTRODUCTION	2017