



STOTHERM MASONRY INSULATION SYSTEM - SS207

- STO ADHESIVE MORTAR
- SELECTED STOTHERM PANELS - 40, 50, 60, 80 & 100mm THICK PANELS
- BASECOAT: STOLEVEL NOVO 4-5mm
- REINFORCEMENT: STOARMAT CLASSIC PLUS: STO EUROPEAN MESH
- REINFORCEMENT: STOARMAT CLASSIC
- FINISHING RENDER: STOLIT K or MP COLOURED FINISHING RENDER - 1.0, 1.5, 2.0 & 3.0mm FLOAT FINISH or MP SPOUNGE or MILANO SMOOTH
- COATING/STOCOLOR MAXICRYL MATT FACADE PAINT LASTIC SATIN FACADE PAINT LOTUSAN MINERAL RESIN PAINT

NOTE:
STOTHERM PANELS CAN BE COUNTERSUNK FROM 60mm PLUS THCKNESSES

SCALE 1:20

STOTHERM MASONRY	STOTHERM MASONRY INSULATION SYSTEM	STM 100
	STOTHERM INSULATION SYSTEM - ISOMETRIC	2017

The information contained on this page is based on our experience and research at the date of issue. The detail is for use by Registered Architects, Licensed Designers or Chartered Engineers to assist in developing project details using Sto Systems. Stoanz Ltd reserve the right to alter or update information at any time without prior notice and it is the responsibility of the designer, project manager or Sto contractor to insure they have and use the current Sto details and specifications on site.