

**SS205M STOTHERM MINERAL MASONRY INSULATION SYSTEM BRANZ APPRAISAL CERTIFICATE NO. 604 INCORPORATING:**

1. 80mm STOTHERM MINERAL NON-COMBUSTABLE FACADE BOARD.
2. STOFLEXYL WATERPROOFING 18kg PAIL PLUS CEMENT EVALUATED BY BRANZ TO MEET AS/NZS4858 AS A WATERPROOFING MEMBRANE IN ACCORDANCE WITH NZBC E2/AS1
3. STOLEVELL NOVO 15kg BAG ADHESIVE RENDER TO ADHERE BOARDS.
4. STOLEVELL NOVO BASECOAT RENDER TO STRAIGHTEN BOARDS,
5. STOLEVELL NOVO RENDER LIGHTWEIGHT MINERAL RENDER COAT USED WITH EUROPEAN MESH AS REINFORCEMENT.
6. STOLIT K or MP COLOURED RENDER 25kg PAIL EUROPEAN FIBRE REINFORCED NON-CEMENT BASED COLOURED FINISHING RENDER AVAILABLE IN STOLIT K 1.0/1.5/2.0/3.0mm FLOAT FINISH & STOLIT MP, MP NATURAL & MILANO FINE FINISH
7. STOCOLOR : STOCOLOR MAXICRYL MATT FACADE PAINT 15lt PAIL  
: STOCOLOR LASTIC SATIN FACADE PAINT 15lt PAIL  
: STOCOLOR LOTUSAN FLAT MINERAL PAINT 15lt PAIL  
: S-PROTECT SC STAY CLEAN SEALER FOR MP or MP NATURAL
8. ALTERNATIVELY USE STOARMAT LIGHTWEIGHT ORGANIC RENDER COAT USED WITH EUROPEAN MESH AS REINFORCEMENT FOR STOLIT MP, MP NATURAL AND MILANO FINISHES.

**SUNDRIES**

80mm STOTHERM MINERAL MASONRY ANCHORS  
STO uPVC CORNER ANGLES, DRIP EDGES, TRAYS, AND FINISHING EDGES.  
STOTHERM 80mm EPS PLINTH PANELS.

<b>STOTHERM MINERAL</b>	<b>STOTHERM MINERAL MASONRY INSULATION SYSTEM</b>	<b>STMI 003</b>
	<b>INTRODUCTION</b>	<b>2017</b>