

STOLITE CONSTRUCTION SYSTEM

THE STOLITE CONSTRUCTION SYSTEM HAS BEEN APPRAISED AS AN EXTERNAL WALL CLADDING SYSTEM FOR BUILDINGS WITHIN THE FOLLOWING SCOPE:

- THE SCOPE LIMITATIONS OF NZBC ACCEPTABLE SOLUTION E2/AS1, PARAGRAPH 1.1; AND,
- CONSTRUCTED WITH TIMBER FRAMING COMPLYING WITH THE NZBC; AND,
- WITH A RISK SCORE OF 0-20, CALCULATED IN ACCORDANCE WITH NZBC ACCEPTABLE SOLUTION E2/AS1, TABLE 2; AND,
- SITUATED IN NZS 3604 WIND ZONES UP TO, AND INCLUDING 'EXTRA HIGH'.

THE STOLITE CONSTRUCTION SYSTEM HAS ALSO BEEN APPRAISED FOR WEATHERTIGHTNESS AND STRUCTURAL WIND LOADING WHEN USED AS AN EXTERNAL WALL CLADDING SYSTEM FOR BUILDINGS WITHIN THE FOLLOWING SCOPE:

- THE SCOPE LIMITATIONS OF NZBC ACCEPTABLE SOLUTION E2/AS1, PARAGRAPH 1.1; AND,
- CONSTRUCTED WITH TIMBER OR STEEL FRAMING COMPLYING WITH THE NZBC; AND,
- SITUATED IN SPECIFIC DESIGN WIND PRESSURES UP TO A MAXIMUM DESIGN DIFFERENTIAL ULTIMATE LIMIT STATE (ULS) OF 2.5 KPa.

STOLITE RENDER SYSTEM

INCORPORATING:

1. 8mm LEVELITE BASECOAT RENDER 20kg BAG
2. STOARMAT MESHED REINFORCEMENT RENDER 23kg BAG
3. STOLIT K or MP COLOURED FINISHING RENDER 25kg PAIL
4. STOCOLOR : MAXICRYL MATT FACADE PAINT 15lt PAIL  
                   : LASTIC SATIN FACADE PAINT 15lt PAIL  
                   : LOTUSAN MINERAL RESIN PAINT 15lt PAIL

<b>STOLITE SYSTEM</b>	<b>STOLITE CONSTRUCTION SYSTEM</b>	<b>SL 006</b>
	<b>INTRODUCTION</b>	<b>2017</b>