



1. SHEET JOINTS MUST NOT COINCIDE WITH EDGE OF JOINERY UNLESS A CONTROL JOINT IS TO BE FORMED.
2. ALL SHEET EDGES SHALL LINE THROUGH AND BE SUPPORTED BY A FRAMING MEMBER.
3. INSTALL SHEETS AS PER DETAILS USING NOMINAL 20x45mm H3.1 TIMBER CAVITY BATTENS
4. STAGGER VERTICAL SHEET JOINTS AT INTERSTOREY JOINT.
5. ALL SHEET EDGES SHALL BE A TIGHT BUTT FIT MESHED WITH 100mm JOINTING TAPE IN BASECOAT.
6. FLASHING AS FOLLOWS
  - HORIZONTAL STO uPVC 12mm CONTROL JOINT AT INTERSTOREY JUNCTIONS
  - STO 8mm VERTICAL CONTROL JOINTS @ 5.4m crs max.
  - INTER-STOREY DRAINED JOINT EVERY THIRD STOREY

SCALE: N.T.S

<b>STOLITE SYSTEM</b>	<b>STOLITE CONSTRUCTION SYSTEM</b>	<b>SL 300</b>
	<b>STOLITE SHEET LAYOUT</b>	<b>2013</b>

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.