



FLEXIBLE FLASHING TAPE  
INSTALLED OVER WALL  
UNDERLAY AT CORNERS  
AIRSEAL ON PEF ROD  
GAP 7.5-8mm APPROX

WALL UNDERLAY  
20mm DRAINED CAVITY  
6mm FIBRE CEMENT SHEET  
STOLITE RENDER SYSTEM  
ADDITIONAL LAYER OF  
FLASHING TAPE LAPPED OVER  
HEAD FLASHING  
VENTED VERMIN  
TRAY min. 15mm UP  
STOLITE CLIP-ON TRAY  
WITH MIN 5mm GAP  
MIN. 5mm GAP REQUIRED  
ALUMINIUM HEAD  
FLASHING WITH 15°  
SLOPE AND 10mm COVER

1. HEIGHT WORK TO UNDERSIDE SOFFIT.  
MEASURE DOOR HEIGHT ON SITE &  
CHECK GARAGE DOOR SPECIFICATIONS  
FOR INTERNAL CORNER REQUIREMENTS
2. SEAL FLASHING FOR VERY HIGH or  
EXTRA HIGH WIND ZONE
3. IN EXTRA HIGH WIND ZONES INCREASE  
FLASHING COVER TO 60mm AND USE A  
RIGID UNDERLAY

SCALE 1:2

<b>STOLITE SYSTEM</b>	<b>STOLITE CONSTRUCTION SYSTEM</b>	<b>SL 408</b>
	<b>GARAGE DOOR - TIMBER HEAD DETAIL</b>	<b>2017</b>