



**E2/AS1 REQUIRES BALCONY & PARAPET WALLS TO BE OFFSET FROM THE MAIN WALL PLAIN TO ALLOW FOR SADDLE FLASHINGS**

BASECOAT  
6mm SHEET ON PACKER

**NOTE:**

STOFLEXYL MESHED WATERPROOFING HAS BEEN TESTED BY **BRANZ** TO MEET **AS/NZS4858** AS REQUIRED BY **E2/AS1**. ALL WALL CAPS (MIN. 10° FALL) ARE TO HAVE STOFLEXYL WATERPROOFING AS SHOWN OVER THE STOLITE BASECOAT PLASTER. STOFLEXYL TO EXTEND 75mm MIN. DOWN THE WALL FACE AND ONTO ADJACENT WALLS

SCALE 1:5

|                       |   |               |
|-----------------------|---|---------------|
| <b>STOLITE SYSTEM</b> | <b>STOLITE CONSTRUCTION SYSTEM</b>                    | <b>SL 506</b> |
|                       | <b>STOFLEXYL MESHED WATERPROOFING CAP - ISOMETRIC</b> | <b>2014</b>   |

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.