



ROOF UNDERLAY
CONTINUOUS TO TOP OF
FLASHING

- 20mm DRAINED CAVITY
- STO STAINLESS STEEL LATH
- STOLITE RENDER SYSTEM
- STO uPVC VENTED FOOT TRAY WITH 15mm DRIP EDGE
- STOPEND FLASHING

- REFER E2/AS1 TABLE 7
- PREFINISHED METAL APRON FLASHING
- PREFINISHED METAL ROOFING OVER UNDERLAY
- SELECTED ROOF UNDERLAY

5mm GAP MAX.
FOR NOTCHED
TURN-DOWN

50mm MIN.FASCIA BACK
FLASHING - SHOWN DASHED

NOTE: CONTRACTOR TO FIT STOPEND FLASHING & HEMMED FLASHING FOR FASCIAS 50mm BEHIND CLADDING, 50mm BEHIND FASCIA. STO CONTRACTOR TO APPLY FINISHED SEALANT JOINT BETWEEN FASCIA & PLASTER. UNDERLAY or FLASHING TAPE OVER FLASHING UPSTAND.

PARAPETS - REFER 500 SERIES - PARAPET DETAILS

SCALE 1:5

STOLITE SYSTEM	STOLITE CONSTRUCTION SYSTEM	SL 702
	INTERSTOREY TRANSVERSE (APRON) ROOF STOPEND	2017

The information contained on this page is based on our experience and research at the date of issue. The detail is for use by Registered Architects, Licensed Designers or Chartered Engineers to assist in developing project details using Sto Systems. Stoanz Ltd reserve the right to alter or update information at any time without prior notice and it is the responsibility of the designer, project manager or Sto contractor to insure they have and use the current Sto details and specifications on site.