



HORIZONTAL PROFILED METAL WALL CLADDING (SPECIFY TYPE, THICKNESS & COATING)

FIXING IN ACCORDANCE WITH E2/AS1

CONTINUOUS CAVITY DRAINAGE STRIP - BY OTHERS

PURPOSE MADE FLASHING (SPECIFY COATING)

MS SEALANT

STOLITE RENDER SYSTEM WITH STOLITE uPVC CLIP ON FLASHING OVER 20mm DRAINED CAVITY ON 6mm FC SHEET

1. REFER TO E2/AS1 FOR COMPLIANT PROFILES AND FLASHINGS
2. HORIZONTAL PROFILE METAL WALL CLADDING IS FIXED ON A **DRAINED CAVITY**
3. VERTICAL PROFILE METAL WALL CLADDING IS **DIRECT FIXED** OVER A ROOF UNDERLAY. FIXINGS IN ACCORDANCE WITH E2/AS1
4. IN EXTRA HIGH WIND ZONES INCREASE FLASHING COVER TO 60mm MIN. AND USE A RIGID UNDERLAY

SCALE 1:2

STOLITE SYSTEM	STOLITE CONSTRUCTION SYSTEM	SL 853
	HORIZ.JUNCTION HORIZ.PROFILED METAL/STOLITE	2017

The information contained on this page is based on our experience and research at the date of issue. The detail is for use by Registered Architects, Licensed Designers or Chartered Engineers to assist in developing project details using Sto Systems. Stoanz Ltd reserve the right to alter or update information at any time without prior notice and it is the responsibility of the designer, project manager or Sto contractor to insure they have and use the current Sto details and specifications on site.