

STOSTUCCO CONSTRUCTION SYSTEM ON STO STAINLESS STEEL LATH

SS808 STOSTUCCO PLASTER SYSTEM BRANZ APPRAISAL CERTIFICATE No.605 INCORPORATING:

1. STO STAINLESS STEEL LATH WITH STO uPVC FLASHING SYSTEM
2. STOFLEXYL MESHED WATERPROOFING 18kg PAIL PLUS CEMENT EVALUATED BY BRANZ TO MEET AS/NZS 4858. WATERPROOFING AS REQUIRED BY E2/AS1
3. LEVELLITE BASE PLASTER 20kg BAG MINERAL LITEWEIGHT BASE PLASTER FOR LEVELLING & STRAIGHTENING WALLS. CAN BE MACHINE APPLIED
4. STOARMAT CLASSIC PLASTER 23kg PAIL. EUROPEAN FIBRE REINFORCED NON-CEMENT BASED CRACK RESISTANT PLASTER USED WITH EUROPEAN MESH AS A REINFORCEMENT PLASTER
5. STOLIT K or MP COLOURED RENDER 25kg PAIL. EUROPEAN FIBRE REINFORCED NON-CEMENT COLOURED FINISHING RENDER AVAILABLE IN 1.0/1.5/2.0 & 3.0mm SIZED TEXTURE and MP or MP NATURAL SPONGE FINISH RENDER
6. STOCOLOR : MAXICRYL MATT FACADE PAINT 15lt PAIL
: LASTIC SATIN FACADE PAINT 15lt PAIL
: LOTUSAN MINERAL RESIN PAINT 15lt PAIL

STOSTUCCO SYSTEM	STOSTUCCO CONSTRUCTION SYSTEM	SS 005
	INTRODUCTION	2014

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.