



1. MS SEALANT TO BE APPLIED TO SILL & JAMB JUNCTIONS
2. SILL FLASHING TO BE PLACED UNDER JAMB FLASHING - CUT SILL FLASHING APPROX. 60mm LONGER THAN WINDOW & FIT TO JAMB FLASHING. ALLOW 30mm EACH SIDE and OVER WANSZ SUPPORT BRACKET
3. ALL 24mm ± GAP BETWEEN WINDOW JOINERY & FRAME FOR STO STUCCO uPVC FLASHINGS

**WARNING:** SOME BRANDS OF ALUMINIUM JOINERY HAVE DRAINAGE VENTS IN THE BOTTOM EDGE OF THE SILL FLANGE. ENSURE DRAINAGE VENTS REMAIN CLEAR.

*CHECK JOINERY POSITION TO FLASHINGS BEFORE FIXING*

SCALE 1:2

<b>STOSTUCCO SYSTEM</b>	<b>STOSTUCCO CONSTRUCTION SYSTEM</b>	<b>SS 402</b>
	<b>ALUMINIUM JOINERY - SILL DETAIL - OPT 2</b>	<b>2014</b>

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.