



STOARMAT PLASTER SYSTEM

TIMBER FRAMING TO NZS 3604
 WALL UNDERLAY MEETING REQUIREMENTS E2/AS1
 STO POREN BRICK VENEER

- S PROTECT WS205 SILANE
- BASECOAT: POREN PLASTER 3/4mm
- STOARMAT CLASSIC PLASTER
- PLUS: STO EUROPEAN MESH
- STOARMAT CLASSIC PLASTER
- STOLIT K & MP COLOURED FINISHING RENDER
- STO COLOR MAXICRYL/STOLASTIC COLOR

WEEP HOLES OR VENTS TO ACHIEVE VENTILATION 1000sq mm PER LINEAL METRE (8 x 75mm holes @ 600mm CENTRES MIN)
 MIN BRICK LAP 150mm
 STO PLASTER DRIP EDGE
 POREN MORTAR
 FLUSH TOOL JOINTS
 REBATE WITH STOFLEXYL OR LIQUID DPM

STO uPVC PLASTER DRIP EDGE
 CONCRETE FOUNDATION AS PER NZS3604 OR SPECIFIC ENGINEERING REQUIREMENTS

STOARMAT PLASTER SYSTEM FOR TWENTY (20) YEAR WARRANTY

SCALE 1:20

STO POREN SYSTEM	STO POREN BRICK VENEER	PB-101
	STOARMAT PLASTER	2014

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.