

**STOPOREN FACADE SYSTEM**  
with StoArmat Render System

THE STOPOREN FACADE SYSTEM HAS BEEN APPRAISED AS AN EXTERNAL WALL CLADDING SYSTEM FOR BUILDINGS WITHIN THE FOLLOWING SCOPE:

- THE SCOPE LIMITATIONS OF NZBC ACCEPTABLE SOLUTION E2/AS1, PARAGRAPH 1.1; AND,
- CONSTRUCTED WITH TIMBER FRAMING COMPLYING WITH THE NZBC; AND,
- WITH A RISK SCORE OF 0-20, CALCULATED IN ACCORDANCE WITH NZBC ACCEPTABLE SOLUTION E2/AS1, TABLE 2; AND,
- SITUATED IN NZS 3604 WIND ZONES UP TO, AND INCLUDING 'EXTRA HIGH'.

THE STOPOREN FACADE SYSTEM HAS ALSO BEEN APPRAISED FOR WEATHERTIGHTNESS AND STRUCTURAL WIND LOADING WHEN USED AS AN EXTERNAL WALL CLADDING SYSTEM FOR BUILDINGS WITHIN THE FOLLOWING SCOPE:

- THE SCOPE LIMITATIONS OF NZBC ACCEPTABLE SOLUTION E2/AS1, PARAGRAPH 1.1; AND,
- CONSTRUCTED WITH TIMBER OR STEEL FRAMING COMPLYING WITH THE NZBC; AND,
- SITUATED IN SPECIFIC DESIGN WIND PRESSURES UP TO A MAXIMUM DESIGN DIFFERENTIAL ULTIMATE LIMIT STATE (ULS) OF 2.5 KPA.

**STOARMAT RENDER SYSTEM**  
Can also be used for additional *strength & reinforcement*

INCORPORATING:

S-PROTECT WS 205 SEALER TO SEAL HEBEL® PANELS

1. STOPOREN RENDER 25kg BAG
2. STOARMAT MESHED REINFORCEMENT COAT
3. STOLIT K : 1.0mm, 1.5mm, 2.0mm & 3.0mm  
COLOURED FINISHING RENDER  
MP : MP COLOURED FINE SPONGE FINISHING RENDER  
MP NATURAL COLOURED FINE SAND FINISHING RENDER  
MILANO SMOOTH COLOURED FINISHING RENDER
4. STOCOLOR : STOCOLOR MAXICRYL MATT FACADE PAINT 15lt PAIL  
: STOCOLOR LASTIC SATIN FACADE PAINT 15lt PAIL  
: STOCOLOR LOTUSAN MINERAL RESIN PAINT 15lt PAIL

<b>STOPOREN FACADE</b>	<b>STOPOREN FACADESYSTEM</b>	<b>PP 007</b>
	<b>STOARMAT PLASTER SYSTEM</b>	<b>2018</b>