

STO POREN FACADE SYSTEM
with StoArmat Render System

THE STO POREN FACADE SYSTEM HAS BEEN APPRAISED AS AN EXTERNAL WALL CLADDING SYSTEM FOR BUILDINGS WITHIN THE FOLLOWING SCOPE:

- THE SCOPE LIMITATIONS OF NZBC ACCEPTABLE SOLUTION E2/AS1, PARAGRAPH 1.1; AND,
- CONSTRUCTED WITH TIMBER FRAMING COMPLYING WITH THE NZBC; AND,
- WITH A RISK SCORE OF 0-20, CALCULATED IN ACCORDANCE WITH NZBC ACCEPTABLE SOLUTION E2/AS1, TABLE 2; AND,
- SITUATED IN NZS 3604 WIND ZONES UP TO, AND INCLUDING 'EXTRA HIGH'.

THE STO POREN FACADE SYSTEM HAS ALSO BEEN APPRAISED FOR WEATHER TIGHTNESS AND STRUCTURAL WIND LOADING WHEN USED AS AN EXTERNAL WALL CLADDING SYSTEM FOR BUILDINGS WITHIN THE FOLLOWING SCOPE:

- THE SCOPE LIMITATIONS OF NZBC ACCEPTABLE SOLUTION E2/AS1, PARAGRAPH 1.1; AND,
- CONSTRUCTED WITH TIMBER OR STEEL FRAMING COMPLYING WITH THE NZBC; AND,
- SITUATED IN SPECIFIC DESIGN WIND PRESSURES UP TO A MAXIMUM DESIGN DIFFERENTIAL ULTIMATE LIMIT STATE (ULS) OF 2.5 KPA.

STO ARMAT RENDER SYSTEM
Can also be used for additional *strength & reinforcement*

INCORPORATING:

S-PROTECT WS 205 SEALER TO SEAL HEBEL® PANELS

1. STO POREN RENDER 25kg BAG
2. STO ARMAT MESHED REINFORCEMENT COAT
3. STOLIT K : 1.0mm, 1.5mm, 2.0mm & 3.0mm
COLOURED FINISHING RENDER
MP : MP COLOURED FINE SPONGE FINISHING RENDER
MP NATURAL COLOURED FINE SAND FINISHING RENDER
MILANO SMOOTH COLOURED FINISHING RENDER
4. STOCOLOR : STOCOLOR MAXICRYL MATT FACADE PAINT 15lt PAIL
: **STOCOLOR** LASTIC SATIN FACADE PAINT 15lt PAIL
: STOCOLOR LOTUSAN MINERAL RESIN PAINT 15lt PAIL

| | | | |
|-----------------------------|---------------------------------|--|---------------|
| STO POREN FACADE | STO POREN FACADE SYSTEM | | PP 007 |
| | STO ARMAT PLASTER SYSTEM | | 2017 |