

**STOPOREN FACADE SYSTEM**  
with StoPoren Render System

THE STOPOREN FACADE SYSTEM HAS BEEN APPRAISED AS AN EXTERNAL WALL CLADDING SYSTEM FOR BUILDINGS WITHIN THE FOLLOWING SCOPE:

- THE SCOPE LIMITATIONS OF NZBC ACCEPTABLE SOLUTION E2/AS1, PARAGRAPH 1.1; AND,
- CONSTRUCTED WITH TIMBER FRAMING COMPLYING WITH THE NZBC; AND,
- WITH A RISK SCORE OF 0-20, CALCULATED IN ACCORDANCE WITH NZBC ACCEPTABLE SOLUTION E2/AS1, TABLE 2; AND,
- SITUATED IN NZS 3604 WIND ZONES UP TO, AND INCLUDING 'EXTRA HIGH'.

THE STOPOREN FACADE SYSTEM HAS ALSO BEEN APPRAISED FOR WEATHERTIGHTNESS AND STRUCTURAL WIND LOADING WHEN USED AS AN EXTERNAL WALL CLADDING SYSTEM FOR BUILDINGS WITHIN THE FOLLOWING SCOPE:

- THE SCOPE LIMITATIONS OF NZBC ACCEPTABLE SOLUTION E2/AS1, PARAGRAPH 1.1; AND,
- CONSTRUCTED WITH TIMBER OR STEEL FRAMING COMPLYING WITH THE NZBC; AND,
- SITUATED IN SPECIFIC DESIGN WIND PRESSURES UP TO A MAXIMUM DESIGN DIFFERENTIAL ULTIMATE LIMIT STATE (ULS) OF 2.5 KPA.

**STOPOREN RENDER SYSTEM**

INCORPORATING:

S-PROTECT WS 205 SEALER TO SEAL HEBEL® PANELS

1. STOPOREN RENDER 25kg BAG
2. STOPLEX W SEALER 10lt CONTAINER
3. STOLIT K : 1.0mm, 1.5mm, 2.0mm & 3.0mm  
COLOURED FINISHING RENDER 25kg PAIL
4. STOCOLOR : STOCOLOR MAXICRYL MATT FACADE PAINT 15lt PAIL  
: STOCOLOR LASTIC SATIN FACADE PAINT 15lt PAIL  
: STOCOLOR LOTUSAN MINERAL RESIN PAINT 15lt PAIL

<b>STOPOREN FACADE</b>	<b>STOPOREN FACADE SYSTEM</b>	<b>PP 008</b>
	<b>STOPOREN PLASTER SYSTEM</b>	<b>2018</b>