



- WALL FRAMING
- WALL UNDERLAY
- STO 20mm VH CAVITY BATTEN
- OVERLAY OF STOFLEXYL MEMBRANE UNDER MESH COAT TO TOP & SIDES 100mm MIN. DOWNTURN OVER LEVELLITE BASE COAT RENDER
- LEVELLITE BASECOAT RENDER
- STOPOREN PANEL CAP
- FLASHING TAPE OR ROOF UNDERLAY OVER H3.1 TIMBER CAPPING PLATE WITH MIN. 10° FALL
- STO 20mm VH CAVITY BATTENS
- WALL UNDERLAY

NOTE:
 APPLY STOFLEXYL MESHED WATERPROOFING OVER BASECOAT
 STOFLEXYL MESHED WATERPROOFING HAS BEEN TESTED BY **BRANZ** TO MEET THE REQUIREMENTS OF **AS/NZS4858** FOR A WATERPROOFING MEMBRANE AS REQUIRED BY **E2/AS1**

SCALE 1:5

STOPOREN FACADE	STOPOREN FACADE SYSTEM	PP 505
	STOFLEXYL MESHED SADDLE FLASHING - ISOMETRIC	2018

The information contained on this page is based on our experience and research at the date of issue. The detail is for use by Registered Architects, Licensed Designers or Chartered Engineers to assist in developing project details using Sto Systems. Stoanz Ltd reserve the right to alter or update information at any time without prior notice and it is the responsibility of the designer, project manager or Sto contractor to insure they have and use the current Sto details and specifications on site.