

**STOARMAT REMEDIAL**  
**PLASTER SYSTEM FOR CRACKED AND LEAKING SUBSTRATES**

**STOARMAT REMEDIAL PLASTER SYSTEM**

**INCORPORATING:**

1. STO CRACK FILLER FINE  
EUROPEAN ELASTIC FILLING MATERIAL FOR CLOSING 1-10mm CRACKS.
2. STOLASTIC FILL  
EUROPEAN MANUFACTURED COLD ELASTOMERIC PASTE FOR BRIDGING AND TAPING CRACKS.
3. STOLASTIC MESH  
SPECIALLY ENGINEERED REINFORCEMENT MESH TO PREVENT CRACK FORMATION WITH HIGH TEAR RESISTANCE TO REINFORCE STOLASTIC FILL.
4. LEVELLITE BASE PLASTER 20kg BAG  
MINERAL LITEWEIGHT BASE PLASTER FOR LEVELLING AND STRAIGHTENING WALLS, CAN BE MACHINE APPLIED.
5. STOARMAT PLASTER 23kg PAIL  
EUROPEAN FIBRE REINFORCED NON-CEMENT BASED CRACK RESISTANT PLASTER USED WITH EUROPEAN MESH AS A REINFORCEMENT PLASTER.
6. STOLIT K or MP COLOURED RENDER 25kg PAIL  
EUROPEAN FIBRE REINFORCED NON-CEMENT BASED COLOURED FINISHING RENDER AVAILABLE IN 1.0/1.5/2.0/3.0mm SIZED TEXTURE AND MP or MP NATURAL SPONGE FINISHED RENDER.
7. STOCOLOR MAXICRYL FACADE PAINT 15lt PAIL  
STOLASTIC COLOR FACADE PAINT 15lt PAIL  
STOLOTUSAN COLOR G 15lt PAIL

<b>REMEDIAL PLASTER SYSTEM</b>	<b>INTRODUCTION</b>	<b>SAR-001</b>
		<b>JULY 2010</b>

The information contained in this detail is based on our experience and testing and represents the latest information available at the date of issue. This detail is intended for use by the design professional and users of Sto products to assist in developing specific project details to be used in conjunction with a Sto Specification. We reserve the right to alter or update information at any time without prior notice & it is the responsibility of the specifier and/or the project manager to insure that they have the current Sto details and specifications.