



Material Safety Data Sheet

StoArmour Facade Panel

Autoclaved Aerated Concrete

Ref. M - 189
 Rev. no. 1
 Prepared Date. 09.02.2022
 Review Date. 09.02.2027

1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Product name:	StoArmour Facade Panel, Autoclaved Aerated Concrete AAC Panel
Recommended use:	Fire Protection, Building Blocks, Noise Suppression, Construction Blocks
Company details:	Stoanz Ltd (trading as Sto New Zealand)
Address:	72 Abel Smith Street, Wellington, New Zealand
Telephone number:	+64 4 801 7794
Emergency telephone no:	Nation Poisons Centre, 0800 POISON, 0800 764 766

2. HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE: The product as supplied is **non-Hazardous**. It is a manufactured article, and is exempt under NZ HSNO.

When concrete products are cut, sawn, abraded or crushed, dust is created which contains crystalline silica, some of which may be respirable (particles small enough to go into the deep parts of the lung when breathed in), and which would be classifiable as **Hazardous** according to NZ EPA.

The following GHS classifications refer **ONLY** to the dust of these products:

GHS Classification	GHS Signal Word	GHS Pictogram/s
Skin Irritation Category 2 Eye Irritation Category 2A Specific Target Organ Toxicity (Single Exposure) Category 3 Specific Target Organ Toxicity (Repeated Exposure) Category 2	WARNING	



Material Safety Data Sheet
StoArmour Facade Panel
Autoclaved Aerated Concrete

Ref. M - 189
 Rev. no. 1
 Prepared Date. 09.02.2022
 Review Date. 09.02.2027

The following GHS Hazard and Precautionary statements refer ONLY to the dust of these products:

GHS Hazard statements	GHS Precautionary statements
H315 – Causes skin irritation H319 – Causes serious eye irritation H335 – May cause respiratory irritation H373 – May cause damage to organs through prolonged or repeated exposure by inhalation	P260 – Do not breathe dust. P264 – Wash thoroughly after handling. P271 – Use only outdoors or in a well-ventilated area. P280 – Wear eye/face protection and protective gloves. P302 + P352 – If on skin, wash with plenty of soap and water. P304 + P340 – If inhaled, remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 – If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 – Call a Poison Centre or doctor if you feel unwell. P332 + P313 – If skin irritation occurs, get medical advice/attention. P337 + P313 – If eye irritation persists, get medical advice/attention. P362 – Take off contaminated clothing and wash before reuse. P403 + P233 – Store in a well-ventilated place and keep container tightly closed.

Autoclaved Aerated Concrete is classified as **Non-Dangerous Goods** according to the NZ Transport of Dangerous Goods on Land.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name:	Proportion:	CAS Number:
Calcium silicate hydrate	<60-80%	1344-95-2
Crystalline silica	20-40%	14808-60-7
Portland cement	10-60%	65997-15-1
Additives	<5%	---

Note: Cement in concrete contains traces (2-20 ppm) of Chromium VI (hexavalent).





Ref. M - 189

Rev. no. 1

Prepared Date. 09.02.2022

Review Date. 09.02.2027

Material Safety Data Sheet

StoArmour Facade Panel Autoclaved Aerated Concrete

4. FIRST AID MEASURES

The following advice refers mainly to exposure to concrete dust following cutting or crushing of product.

Swallowed:	Rinse mouth and lips with water. Do not induce vomiting. If symptoms persist, seek medical attention.
Eyes:	Flush thoroughly with flowing water, while holding eyelids open, for 15 minutes to remove all traces. If symptoms such as irritation or redness persist, seek medical attention.
Skin:	Remove heavily contaminated clothing. Wash off skin thoroughly with water. Use a mild soap if available. Shower if necessary. Seek medical attention for persistent redness, irritation or burning of the skin.
Inhaled:	Remove to fresh air, away from dusty area. If symptoms persist, seek medical attention.
Advice to Doctor:	Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	Use carbon dioxide, foam, dry chemical or water spray as required for fire in surrounding materials.
Specific hazards:	None
Special protective equipment and precautions for firefighters:	As required for fire in surrounding materials.
HAZCHEM Code:	None Allocated

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:	Avoid generating dust. Recommendations on Exposure Controls / Personal Protection (see Section 8 below) should be followed during spill clean-up if conditions are dusty.
Environmental precautions:	None required.
Methods and materials for containment and cleaning up:	Collect and reuse where possible. Dust is best cleaned up by vacuum device to avoid making dust airborne. Wetting down before sweeping up dust may be a useful control measure.



Ref. M - 189

Rev. no. 1

Prepared Date. 09.02.2022

Review Date. 09.02.2027

Material Safety Data Sheet

StoArmour Facade Panel Autoclaved Aerated Concrete

7. HANDLING AND STORAGE

Precautions for safe handling: Concrete is a heavy material, and appropriate control of manual handling risk is required. Manual handling should be in accordance with Manual Handling Regulations and Codes.

Conditions for safe storage: No special requirements. Safety aspects of stockpiles and storage areas require risk assessment and control.

Incompatibilities: None

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Standards: Workplace Exposure Standards and Biological Exposure Indices, NZ Department of Labour
 Crystalline silica (quartz): TWA – 0.1 mg/m³ respirable dust. (≤ 7 microns particle equivalent aerodynamic diameter)
 Calcium silicate dust: TWA - 10 mg/m³
 Portland cement: TWA – 10 mg/m³ as inspirable dust
 Total dust (of any type or particle size): TWA - 10 mg/m³

Notes on Exposure Standards: All occupational exposures to atmospheric contaminants should be kept to as low a level as is workable (practicable) and in all cases to below the Workplace Exposure Standard (WES).
 TWA (Time Weighted Average): the time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

Biological Limit Values: No biological limit allocated.



Material Safety Data Sheet
StoArmour Facade Panel
Autoclaved Aerated Concrete

Ref. M - 189
 Rev. no. 1
 Prepared Date. 09.02.2022
 Review Date. 09.02.2027

ENGINEERING CONTROLS

<p><input type="checkbox"/> Ventilation:</p>	<p>When dry concrete dust is present, ensure exposures to respirable crystalline silica (quartz) are maintained below WES. Work in the open air and external openings (such as doors and windows in buildings) generally provides adequate ventilation. Local mechanical ventilation or extraction may be required in areas where dust could escape into the working environment. Local dust extraction and collection may be used, if necessary, to control airborne dust levels. Hand tools generate less dust when cutting, drilling or sanding. If power tools are used they should be fitted with efficient and well maintained dust extraction devices. If generated dust cannot be avoided, follow personal protection recommendations.</p>
<p><input type="checkbox"/> Special Consideration for Repair &/or Maintenance of Contaminated Equipment:</p>	<p>Recommendations on Exposure Control and Personal Protection should be followed. When dry concrete dust is present, ensure exposures to respirable crystalline silica (quartz) are maintained below WES. Where possible vacuum or wash down all gear, equipment or mobile plant prior to maintenance and repair work. If compressed air cleaning cannot be avoided, wear eye and respiratory protection and clothing as listed below.</p>

PERSONAL PROTECTION

<p><input type="checkbox"/> Personal Hygiene</p>	<p>Wash hands before eating, drinking, using the toilet, or smoking. Wash work clothes regularly.</p>
<p><input type="checkbox"/> Skin Protection:</p>	<p>Wear loose comfortable clothing and gloves (standard duty leather or equivalent NZS 2161).</p>
<p><input type="checkbox"/> Eye Protection:</p>	<p>Safety glasses with side shields or safety goggles (NZS 1336) or a face shield should be worn.</p>
<p><input type="checkbox"/> Respiratory Protection:</p>	<p>None required if engineering and handling controls are adequate to minimize dust generation and dust exposure. Where engineering and handling controls are not enough to minimise exposure to dust, personal respiratory protection may be required.</p> <p>The type of respiratory protection required depends primarily on the concentration of the respirable crystalline silica dust in the air, and the frequency and length of exposure time. Amount of exertion required during the work, and personal comfort are other considerations in choice of respirator. A suitable P1 or P2 particulate respirator chosen and used in accordance with NZS 1715 and 1716 may be sufficient for many situations, but where high levels of dust are encountered, more efficient cartridge-type or powered respirators or supplied-air helmets or suits may be necessary. Use only respirators that bear the New Zealand Standards mark and are fitted and maintained correctly.</p>



Material Safety Data Sheet

StoArmour Facade Panel

Autoclaved Aerated Concrete

Ref.	M - 189
Rev. no.	1
Prepared Date.	09.02.2022
Review Date.	09.02.2027

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Off-white blocks

Odour: No Odour

Odour threshold: Not applicable

pH: 8-10

Melting point/Freezing point: Not determined

Initial boiling point and range: Not applicable

Vapour pressure: Not applicable

Vapour density: Not applicable

Specific gravity (Relative density): 0.4-0.7

Solubility: Not soluble

Evaporation rate: Not applicable

Partition coefficient (n-octanol/water): Not applicable

Viscosity: Not applicable

Flammability: Not applicable

Flash point: Not applicable

Upper/lower flammability or explosive limits: Not applicable

Auto-ignition temperature: Not applicable

Decomposition temperature: Not determined

% Volatiles: 0%

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Hazardous reactions: None

Conditions to avoid: Dust generation

Incompatible Materials: None

Hazardous Decomposition Products: None



Ref. M - 189

Rev. no. 1

Prepared Date. 09.02.2022

Review Date. 09.02.2027

Material Safety Data Sheet

StoArmour Facade Panel Autoclaved Aerated Concrete

11. TOXICOLOGICAL INFORMATION

The following advice refers mainly to exposure to concrete dust following cutting or crushing of product. Health effects information is based on reported effects in use from international reports.

Health Effects: Acute (short term)

Swallowed: Unlikely under normal industrial use, but swallowing the dust from this product may result in abdominal discomfort.

Eyes: Dust is irritating to the eyes causing watering and redness. Exposure to dust may aggravate pre-existing eye conditions.

Skin: The dust from this product, particularly in association with heat and sweat, may cause irritation. The dust is not absorbed through the skin but, may be mildly irritating and drying to the skin due to its physical characteristics.

Inhaled: Dust is mildly irritating to the nose, throat and respiratory tract and may cause coughing and sneezing. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.

Health Effects: Chronic (long term)

Eyes: Dust may cause irritation and inflammation of the eyes and aggravate pre-existing eye conditions.

Skin: Repeated heavy contact with the dust may cause drying of the skin and can result in skin rash (dermatitis) typically affecting the hands. Over time this may become chronic and can also become infected.

Inhaled: Repeated exposure to the dust may result in increased nasal and respiratory secretions and coughing. Inflammation of lining tissue of the respiratory system may follow repeated exposure to high levels of dust with increased risk of bronchitis and pneumonia.

Material Safety Data Sheet

StoArmour Facade Panel

Autoclaved Aerated Concrete

Ref.	M - 189
Rev. no.	1
Prepared Date.	09.02.2022
Review Date.	09.02.2027

Additional Notes

Long Term Effects: Long term occupational over-exposure or prolonged breathing-in (or inhalation) of crystalline silica dust at levels above the WES carries the risk of causing serious and irreversible lung disease, including bronchitis, and silicosis (scarring of the lung). It may also increase the risk of other irreversible and serious disorders including scleroderma (a disease affecting the skin, joints, blood vessels and internal organs) and other auto-immune disorders.

Any respirable fraction present in dust generated from this product has not been shown to be a carcinogenic risk.

Special Toxic Effects: Inhalation of dust, including crystalline silica dust, is considered by medical authorities to increase the risk of lung disease due to tobacco smoking.

Acute Toxicity Data

No specific toxicology data available, but toxicity of this product is anticipated to be very low with LD50 >5,000mg/kg.

12. ECOLOGICAL INFORMATION

Eco-toxicity: Products as delivered are not biodegradable, have low ecotoxicity and are not regarded as posing any ecological risk. Crushed product and dust may form a mildly alkaline or neutral slurry when mixed with water.

Persistence and Degradability: Product is persistent and would have a low degradability.

Bioaccumulative potential: There is no evidence to suggest bioaccumulation will occur.

Mobility in soil: A low mobility would be expected in a landfill situation.

13. DISPOSAL CONSIDERATIONS

Product: Autoclaved Aerated Concrete can be treated as a common waste for disposal or dumped into a landfill site in accordance with local authority guidelines. Crushed product and dust should be kept out of storm water and sewer drains.

Measures should be taken to prevent dust generation during disposal, and exposure and personal precautions should be observed (see Section 8 above).

Material Safety Data Sheet

StoArmour Facade Panel

Autoclaved Aerated Concrete

Ref.	M - 189
Rev. no.	1
Prepared Date.	09.02.2022
Review Date.	09.02.2027

14. TRANSPORT INFORMATION

UN number: None allocated

UN Proper Shipping Name: None allocated

Class and Subsidiary Risk : None allocated

Packaging Group: None allocated

Special Precautions for User: None

HAZCHEM code: None allocated

15. REGULATORY INFORMATION

HSNO approval number: This is a manufactured article, and is exempt under NZ HSNO

Poisons Schedule: None Scheduled

16. OTHER INFORMATION

For further information on this product, please contact:

Stoanz Limited (trading as Sto New Zealand) 72 Abel Smith Street, Te Aro, Wellington, 6011, New Zealand

Ph: +64 4 801 7794

Fax: +64 4 3849828

ADDITIONAL INFORMATION:

New Zealand Standards References:

NZS 1336 Recommended Practices for Occupational Eye Protection

NZS 1715 Selection, Use and Maintenance of Respiratory Protective Devices

NZS 1716 Respiratory Protective Devices

NZS 2161 Occupational Protective Gloves

NZS 5433 Transport of Dangerous Goods on Land

Other References:

NOHSC:1008 (2004) Approved Criteria for Classifying Hazardous Substances

Model Code of Practice Preparation of Safety Data Sheets for Hazardous Chemicals, December 2011, Safe



Material Safety Data Sheet
StoArmour Facade Panel
Autoclaved Aerated Concrete

Ref. M - 189
 Rev. no. 1
 Prepared Date. 09.02.2022
 Review Date. 09.02.2027

Work Australia.

Model Code of Practice:	Labelling of Workplace Hazardous Chemicals, December 2011, Safe Work Australia.
Model Code of Practice:	Managing Risks Of Hazardous Chemicals In The Workplace, July 2012, Safe Work Australia.
WHS	Guidance on the Classification of Hazardous Chemicals under the WHS Regulations, April 2012, Safe Work Australia.
HSNO CoP 8-1	Code of Practice for the Preparation of Safety Data Sheets, September 2006, NZ EPA.
WES	Workplace Exposure Standards and Biological Exposure Indices, 6th Edition, July 2011, NZ Department of Labour.
NZ CCID	Chemical Classification and Information Database (CCID), internet advisory service, NZ EPA.
GHS	Globally Harmonized System of Classification and Labelling of Chemicals (GHS), 3rd revised edition, United Nations, New York and Geneva, 2009.
GHS	Understanding the Globally Harmonized System of Classification and Labelling of Chemicals (GHS), United Nations, New York and Geneva, 2010.

17. AUTHORISATION

Authorised by: Safety Improvement Manager - Stoanz Ltd
 Date of Issue: 09/02/2022

Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action as a result of this information.