

Ref. MA10000283/

# Material Safety Data Sheet

Rev. no. 1.3

## StoLevell Uni

Prepared Date. 31.10.2019

Review Date. 16.12.2024

### 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

**Product name:** StoLevell Uni

**Recommended use:** Dry Mortar for Coating

**Company details:** Stoanz Ltd

**Address:** 72 Abel Smith Street, Wellington, New Zealand

**Telephone number:** +64 4 801 7794

**Emergency telephone no:** Nation Poisons Centre, 0800 POISON, 0800 764 766

### 2. HAZARDS IDENTIFICATION

**Hazard classification:** Non Hazardous according to NZ HSNO Regulations.  
Not regulated under NZS5433 for land transportation.

**Hazard statement code:** H315: Causes skin irritation  
H318: Causes serious eye damage  
H335: May cause respiratory irritation

**Prevention statements:** P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P270: Do not eat, drink or smoke when using this product.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Response statements:** P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P302+352+361: IF ON SKIN: Wash with plenty of water. Take off immediately all contaminated clothing.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.  
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

**Storage:** P401: Store in original container

**Disposal:** P501: Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Description:** Cementitious and calcareous factory-made mortar.

Ref. MA10000283/

# Material Safety Data Sheet

Rev. no. 1.3

## StoLevell Uni

Prepared Date. 31.10.2019

Review Date. 16.12.2024

Component	CAS Number	Content
Portland Cement	65997-15-1 266-043-4	≥10 - <20
Calcium Hydroxide	1305-62-0 215-137-301-21119475151-45-XXXX	<5
Quartz (particle of sand <12 µm less than 1%)	14808-6067 238-878-4	≥25 - <50

### 4. FIRST AID MEASURES

**Description of necessary first aid measures:** In the case of accident or if you unwell, seek medical advice immediately (show the label where possible).  
Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

**Workplace facilities required instructions:**

Inhalation  
Move to fresh air.  
If symptoms persist, call a physician.

Skin Contact  
Take off all contaminated clothing and shoes immediately.  
Wash off immediately with soap and plenty of water.  
If skin irritation persists, call a physician.

Eye Contact  
Remove contact lens.  
Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Consult a physician.

Ingestion  
Rinse Mouth.  
In conscious, drink plenty of water.  
DO NOT induce vomiting.  
Obtain medical attention.

**Notes for medical personal:** Treat symptomatically

### 5. FIRE FIGHTING MEASURES

**Type of hazard:** Exposure to decomposition products may be a health hazard.  
When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke.

**Fire hazard properties extinguishing media & methods:** Not Combustible.  
Not Applicable.

Ref. MA10000283/

# Material Safety Data Sheet

Rev. no. 1.3

## StoLevell Uni

Prepared Date. 31.10.2019

Review Date. 16.12.2024

Protective clothing: Not Applicable

### 6. ACCIDENTAL RELEASE MEASURES

**Procedures to be covered:** [Environmental Precautions](#)  
 The product should not be allowed to enter drains, water courses or the soil.  
 If the product contaminates rivers, lakes or drains inform respective authorities.

[Methods for Cleaning Up](#)  
 Use mechanical handling equipment.  
 Moisten and remove.  
 Avoid raising dust-vacuum-clean instead of sweeping in rooms.  
 Dispose contaminated material as waste according to section 13. Clean contaminated surface thoroughly.

### 7. HANDLING AND STORAGE

**Handling Practices:** [Advice on safe handling](#)  
 Avoid dust formation.  
 With sack goods and the use of open mixing containers, fill water first, then carefully allow the dry mortar to run in. Keep fall height low. Start-up mixer slowly.  
 DO NOT press empty sacks or compact in e.g. Larder sack.  
 Large loads of over 25kg should be moved not by hand but with the aid of mechanical equipment only. Depending on the employee's age, gender and constitution and the frequency with which loads are lifted and carried, they may also induce a high level of strain at lower weights.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 DO NOT re-use empty containers.

Wash hands before breaks and at the end of workday.  
 When using do not eat, drink or smoke.  
 Avoid contact with the skin and the eyes.

**Storage:** [Requirements for storage areas and containers](#)  
 Store in original containers.  
 Keep in a dry place.  
[Further information on storage conditions](#)  
 Protect from humidity and water.  
 Manufacturer's notes on storage conditions and product life must be observed.  
[Advice on Common Storage](#)  
 No materials to be especially mentioned.  
[Specific Use\(s\)](#)  
 For further information, also see the Technical Data Sheet.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Workplace exposure guidelines:** Note: Contains no substances with community workplace limits. Observe country-specific regulations

Ref. MA10000283/

# Material Safety Data Sheet

Rev. no. 1.3

## StoLevell Uni

Prepared Date. 31.10.2019

Review Date. 16.12.2024

### Exposure limit(s):

Component		CAS-No.
Basis	Type	Control Parameters
Quartz (particle of sand <12 µm less than 1%)		14808-60-7
Additional advice	Longer and/or strong inhalation of alveolae penetrating fine quartz dust can lead to pneumoconiosis, also known as silicosis.  The effect of quartz dust (including cristobalite, tridymite) occurs over a long period of time and is significantly dependent on the dust exposure dose, which in turn is dependent on the average dust concentration (respirable fraction) the individual is exposed to over a long period of time.	
Calcium Hydroxide		1305-62-0
91-322-EEC	Limit Value – eight hours	5 mg/m <sup>3</sup>
Additional advice	Existing scientific data on health effects appear to be particularly limited.  Indicative.	

### Personal protective equipment (PPE):

Washing occasion / water for cleaning of eyes and skin should be present.  
Maintain air concentrations below occupational exposure standards.

### Specification for equipment: Respiratory Protection

Avoid inhalation of particles.  
The use of a dust mask FFP2 is necessary when the Exposure Limit Values is exceeded.

### Hand Protection

Nitrile coated cotton gloves  
Break through time: 480 min Minimum  
Minimum Thickness: 0.8 mm  
After washing hands replace lost skin oils with oil containing skin creams. Take note of the information given by the producer concerning permeability and break through times, and of special work place conditions (mechanical strain, duration of contact).  
The choice of an appropriate glove does not only depend on its materials but also on other quality features and is different from one producer to the other.  
Observe manufacturer's recommendations.

### Eye/Face Protection

Wear tightly fitting safety goggles.

### Body Protection

Long sleeved clothing

### General hygiene:

Wash hands before breaks and at the end of the workday.

Ref. MA10000283/

# Material Safety Data Sheet

Rev. no. 1.3

## StoLevell Uni

Prepared Date. 31.10.2019

Review Date. 16.12.2024

Remove and wash contaminated clothing and gloves, including the inside, before re-use.  
 Avoid contact with the skin and the eyes.  
 Keep away from food, drink and animal feeding stuffs.  
 When using, DO NOT eat, drink or smoke.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State:</b>	Powder
<b>Colour:</b>	Light Cream
<b>Odour:</b>	None
<b>pH:</b>	Ca. 11.0-13.5 at 20°C (as aqueous solution)
<b>Melting Point/Range:</b>	Not applicable
<b>Boiling Point &amp; Boiling Range:</b>	Not applicable
<b>Flash point:</b>	Not applicable
<b>Auto-Flammability:</b>	Not auto-flammable
<b>Density:</b>	ca. 1.150-1.500 kg/cm <sup>3</sup> at 20°C
<b>Water Solubility:</b>	Slightly Soluble

### 10. STABILITY AND REACTIVITY

<b>Thermal decomposition:</b>	No decomposition if stored and applied as directed.
<b>Hazardous reactions:</b>	Fire will produce dense black smoke containing hazardous combustion products.
<b>Hazard decomposition:</b>	No decomposition if stored and applied as directed.

### 11. TOXICOLOGICAL INFORMATION

<b>Data and interpretation:</b>	<u>Acute Oral Toxicity</u> No data available <u>Acute Inhalation Toxicity</u> No data available <u>Acute Dermal Toxicity</u> No data available <u>Skin Irritation</u> Irritation to respiratory system and skin <u>Eye Irritation</u> Severe eye irritation Risk of serious damage to eyes <u>Sensitisation</u> No sensitizing effects known.
---------------------------------	---

Ref. MA10000283/

# Material Safety Data Sheet

Rev. no. 1.3

## StoLevell Uni

Prepared Date. 31.10.2019

Review Date. 16.12.2024

### Other Information

The product is not tested as such. The preparation is classified according to the conventional method (analysis method EU Guideline 1999/45/EG) and according to toxicological risks.

## 12. ECOLOGICAL INFORMATION

**Eco-toxicological effects:** Do no empty into drains.  
Eco-toxic effects, in particular aquatic toxicity are only possible with the release of larger quantities in connection with water by pH value movement.

**Toxicity:**

Toxicity to Fish – Calcium Hydroxide  
LC 50  
Species: Fish  
Dose: 50.6 mg/l  
Exposure time: 96 h

Toxicity to Algae – Calcium Hydroxide  
EC 50  
Species: Algae  
Dose: 184.6 mg/l  
Exposure time: 72 h

NOEC  
Species: Algae  
Dose: 48.0 mg/l  
Exposure time: 72 h

Toxicity to Daphnia – Calcium Hydroxide  
EC 50  
Species: Daphnia  
Dose: 49.1 mg/l  
Exposure time: 48 h

**Persistence & Degradability** Biodegradability – Calcium Hydroxide  
Not Applicable

**Bio accumulative Potential** Bioaccumulation  
Not Applicable

**Mobility in Soil** Product: Mobility  
Not Applicable

**Results of PBT & vPvB Assessment** Product: Assessment  
This mixture contains no substance considered to be persistent, bio accumulating nor toxic (PBT)., This mixture contains no substance considered to be very persistent nor very bio accumulating (vPvB).

## 13. DISPOSAL CONSIDERATIONS

**Product:** The user is responsible for proper coding and marking of any waste.

Ref. MA10000283/

Rev. no. 1.3

Prepared Date. 31.10.2019

Review Date. 16.12.2024

# Material Safety Data Sheet

## StoLevell Uni

Dispose of as special waste in compliance with local and national regulations.

Opened and leftover materials can be used later. Only materials no longer suitable for use should be mixed with water and allowed to harden. Hardened material can be disposed of as normal trade or site waste. Unhardened leftover product should be disposed of under the recommended waste code.

**Un-cleaned packaging:** Empty packaging should be recycled through disposal systems.

**Code of waste (EWC):** 17.01.01: concrete  
10.13.14: waste concrete and concrete sludge

### 14. TRANSPORT INFORMATION

**Overland transport:** Not dangerous goods in the meaning of ADR/RID, ADNR, IMDG-Code, ICAO/IATA-DGR

**Shipment by sea: (IMDG/GGVSee)** Not dangerous goods in the meaning of ADR/RID, ADNR, IMDG-Code, ICAO/IATA-DGR

**Air transport: (ICAO/IATA)** Not dangerous goods in the meaning of ADR/RID, ADNR, IMDG-Code, ICAO/IATA-DGR

**Remarks:**

### 15. REGULATORY INFORMATION

**HSNO approval number:** Non Hazardous according to NZ HSNO Regulations

**HSNO controls:** Non Hazardous according to NZ HSNO Regulations

**Occupational restrictions:** Non Hazardous according to NZ HSNO Regulations

### 16. OTHER INFORMATION

**Miscellaneous information:** It is possible in the interim period that you will find different markings on packaging compared with the Material Safety Data Sheet until stocks have been depleted. We ask for your understanding in this matter.

Changes from the previous version are indicated with markings on the left ed. The details in this Safety Data Sheet are equivalent to our current knowledge and comply with the national as well as the EC legislation. The working conditions of the user however escape our knowledge and control. The user is responsible for the observance of all necessary legal regulations. The details in this Safety Data Sheet describe the safety requirements of our product and are no guarantee for the product characteristics.

**References:**



# Material Safety Data Sheet

---

## StoLevell Uni

Ref.	MA10000283/
Rev. no.	1.3
Prepared Date.	31.10.2019
Review Date.	16.12.2024